

Movement Table

<i>Breach Opening</i>	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
	(150mm)	(200mm)	(250mm)	(300mm)	(350mm)	(400mm)	(450mm)	(500mm)	(550mm)	(600mm)
<i>Manufactured F/F</i>	6.5"	8.5"	11"	13"	15"	17"	19"	21"	23"	25"
	(163mm)	(215mm)	(275mm)	(325mm)	(375mm)	(452mm)	(475mm)	(525mm)	(575mm)	(625mm)
<i>Bolt Gauge (Normal)</i>	3"	4"	5"	6"	6.75"	6.75"	6.75"	6.75"	6.75"	6.75"
	(17mm)	(100mm)	(125mm)	(150mm)	(170mm)	(170mm)	(170mm)	(170mm)	(170mm)	(170mm)
<i>Set Back (Minimum)</i>	2.25"	2.5"	3.25"	3.5"	3.625"	3.875"	4"	4.25"	4.375"	4.5"
	(57mm)	(65mm)	(82mm)	(88mm)	(92mm)	(96mm)	(100mm)	(105mm)	(109mm)	(113mm)
<i>Axial Compression (Operating)</i>	1.5"	2.25"	3.25"	4"	4.75"	5.625"	6.25"	7"	7.5"	8.5"
	(40mm)	(60mm)	(80mm)	(100mm)	(120mm)	(140mm)	(155mm)	(175mm)	(190mm)	(210mm)
<i>(Excursion)</i>	3.25"	4.375"	5.5"	6.5"	7.5"	8.5"	9.5"	10.5"	11.5"	12.5"
	(80mm)	(110mm)	(140mm)	(165mm)	(190mm)	(215mm)	(240mm)	(265mm)	(290mm)	(315mm)
<i>Axial Extension (Operating)</i>	0.5"	0.5"	1"	1"	1"	1"	1"	1"	1"	1"
	(15mm)	(15mm)	(25mm)	(25mm)	(25mm)	(25mm)	(25mm)	(25mm)	(25mm)	(25mm)
<i>(Excursion)</i>	5% Stretch allowed for Wire-F; 20% Stretch allowed for Wire									
<i>Resultant Lateral (Operating)</i>	1.5"	2.25"	3.25"	4"	4.75"	5.625"	6.25"	7"	7.5"	8.5"
	(40mm)	(60mm)	(80mm)	(100mm)	(120mm)	(140mm)	(155mm)	(175mm)	(190mm)	(210mm)
<i>(Excursion)</i>	2.375"	3.375"	4.375"	5.375"	6.25"	7"	7.5"	8.5"	9.5"	10.6"
	(60mm)	(85mm)	(110mm)	(135mm)	(155mm)	(175mm)	(190mm)	(215mm)	(240mm)	(265mm)

Movement Types

