

PARKER TECHSEAL UL LISTED ELASTOMERS

Compound	N0497	N0674	N0757	N7798	N7010	V1262	V0747	V0884	V1163	V1263	V1264	S7442	S7395	S7426	S7310	S7416
Durometer	70	70	70	80	90	65	75	75	75	75	90	40	60	60	70	70
Color	Black	Black	Black	Black	Black	Black	Black	Brown	Black	Black	Black	Rust	Grey	Rust	Green	Rust
Suitable for use in UL262 Applications																
Heated Fuel Oil																
UL497 with Minimum Tensile 1200 PSI & Elongation not less than 300%																
UL 157 JMLU2 with a minimum Service Temperature of -60C																
UL 94 HB Flame Retardant																
UL94 V-0 Flame Retardant																
Liquefied Petroleum Gas (LP Gas)																
Anhydrous Ammonia																
Diesel Fuel, Fuel or lubricating Oil																
Manufactured Gas or Natural Gas																
Naphtha or Kerosene																
Dry Chemical, Carbon Dioxide, Water																
Suitable for 0-100% Ethanol or Methanol / Gasoline Blends																
Suitable for 0-20% ETBE / Gasoline Blends																
Suitable for 0-20% TAME / Gasoline Blends																
Suitable for 0-20% MTBE / Gasoline Blends																
Suitable for Gasoline & alcohol blends with a full conc. range for Methanol																
Suitable for 85% Methano l/ Gasoline blends																
Suitable for 0-30% Ethanol / Gasoline blends																
Suitable for Gasoline & alcohol blends with a max of 20% Ethanol/Methanol blend																
Gasoline / Alcohol Blends																
Gasoline																
Extinguishing Agents																
Atmospheric Ozone																