












































FlexiLip™, FlexiCase™ and FlexiSeal®

FlexiLip, FlexiCase and **FlexiSeal** PTFE seals extend the Parker application range by providing coverage where operating conditions exceed the capabilities of elastomeric lip material. Conditions such as high speed and high pressure and requirements for chemical resistance and low torque are easily accommodated by one of our 50 standard profiles. The typical size range is for shaft diameters from 0.125" (3mm) to 16" (406mm).

FlexiLip, FlexiCase and FlexiSeal Rotary Profiles

FlexiLip, FlexiCase and FlexiSeal Rotary Profiles							
 LFN-N	 LEN-N	 LDN-N	 LMN-N	 LFE-N	 LEE-N	 LDE-N	 LGN-N
 LFN-S	 LEN-S	 LDN-S	 LMN-S	 LFE-S	 LEE-S	 LDE-S	 LGN-S
 CFN	 CFE	 CMN	 CME	 CEN	 CEE	 CDN	 CDE
 CGN	 CGE	 CJN	 CJE	 CHN	 CHE	 FCC-V	 FCS-V
 FCC-C	 FCS-C	 FHC-V	 FHS-V	 FHC-C	 FHS-C	 FFC-V	 FFS-V
 FFC-C	 FFS-C	 FFN-H					