

JIS B2401 Sizes

JIS B2401	Thickness		Inner Diameter			
	W (mm)		d (mm)			
P 3	1.9	±0.08	2.8	±0.14		
P 4			3.8	±0.14		
P 5			4.8	±0.15		
P 6			5.8	±0.15		
P 7			6.8	±0.16		
P 8			7.8	±0.16		
P 9			8.8	±0.17		
P 10			9.8	±0.17		
P 10A			2.4	±0.09	9.8	±0.17
P 11					10.8	±0.18
P 11.2	11.0	±0.18				
P 12	11.8	±0.19				
P 12.5	12.3	±0.19				
P 14	13.8	±0.19				
P 15	14.8	±0.20				
P 16	15.8	±0.20				
P 18	17.8	±0.21				
P 20	19.8	±0.22				
P 21	3.5	±0.10	20.8	±0.23		
P 22			21.8	±0.24		
P 22A			21.7	±0.24		
P 22.4			22.1	±0.24		
P 24			23.7	±0.24		
P 25			24.7	±0.25		
P 25.5			25.2	±0.25		
P 26			25.7	±0.26		
P 28			27.7	±0.28		
P 29			28.7	±0.29		
P 29.5	29.2	±0.29				
P 30	29.7	±0.29				
P 31	8.4	±0.15	30.7	±0.30		
P 31.5			31.2	±0.31		
P 32			31.7	±0.31		
P 34			33.7	±0.33		
P 35			34.7	±0.34		
P 35.5			35.2	±0.34		
P 36			35.7	±0.34		
P 38			37.7	±0.37		
P 39			38.7	±0.37		
P 40			39.7	±0.37		
P 41	3.1	±0.10	40.7	±0.38		
P 42			41.7	±0.39		
P 44			43.7	±0.41		
P 45			44.7	±0.41		
P 46			45.7	±0.42		

JIS B2401	Thickness		Inner Diameter	
	W (mm)		d (mm)	
P 48	3.5	±0.10	47.7	±0.44
P 49			48.7	±0.45
P 50			49.7	±0.45
P 48A	5.7	±0.13	47.6	±0.45
P 50A			49.6	±0.45
P 52			51.6	±0.47
P 53			52.6	±0.48
P 55			54.6	±0.49
P 56			55.6	±0.50
P 58			57.6	±0.52
P 60			59.6	±0.53
P 62			61.6	±0.55
P 63			62.6	±0.56
P 65	8.4	±0.15	64.6	±0.57
P 67			66.6	±0.59
P 70			69.6	±0.61
P 71			70.6	±0.62
P 75			74.6	±0.65
P 80			79.6	±0.69
P 85			84.6	±0.73
P 90			89.6	±0.77
P 95			94.6	±0.81
P 100			99.6	±0.84
P 102	3.1	±0.10	101.6	±0.85
P 105			104.6	±0.87
P 110			109.6	±0.91
P 112			111.6	±0.92
P 115			114.6	±0.94
P 120			119.6	±0.98
P 125			124.6	±1.01
P 130			129.6	±1.05
P 132			131.6	±1.06
P 135			134.6	±1.09
P 140	8.4	±0.15	139.6	±1.12
P 145			144.6	±1.16
P 150			149.6	±1.19
P 150A			149.5	±1.19
P 155			154.5	±1.23
P 160			159.5	±1.26
P 165			164.5	±1.30
P 170			169.5	±1.33
P 175			174.5	±1.37
P 180			179.5	±1.40
P 185	184.5	±1.44		
P 190	189.5	±1.48		
P 195	194.5	±1.51		

JIS B2401	Thickness		Inner Diameter	
	W (mm)		d (mm)	
P 200	8.4	±0.15	199.5	±1.55
P 205			204.5	±1.58
P 209			208.5	±1.61
P 210			209.5	±1.62
P 215			214.5	±1.65
P 220			219.5	±1.68
P 225			224.5	±1.71
P 230			229.5	±1.75
P 235			234.5	±1.78
P 240			239.5	±1.81
P 245	3.1	±0.10	244.5	±1.84
P 250			249.5	±1.88
P 255			254.5	±1.91
P 260			259.5	±1.94
P 265			264.5	±1.97
P 270			269.5	±2.01
P 275			274.5	±2.04
P 280			279.5	±2.07
P 285			284.5	±2.10
P 290			289.5	±2.14
P 295	8.4	±0.15	294.5	±2.17
P 300			299.5	±2.20
P 315			314.5	±2.30
P 320			319.5	±2.33
P 335			334.5	±2.42
P 340			339.5	±2.45
P 355			354.5	±2.54
P 360			359.5	±2.57
P 375			374.5	±2.67
P 385			384.5	±2.73
P 400	399.5	±2.82		
G 25	3.1	±0.10	24.4	±0.25
G 30			29.4	±0.29
G 35			34.4	±0.33
G 40			39.4	±0.37
G 45			44.4	±0.41
G 50			49.4	±0.45
G 55			54.4	±0.49
G 60			59.4	±0.53
G 65			64.4	±0.57
G 70			69.4	±0.61
G 80	8.4	±0.15	79.4	±0.69
G 85			84.4	±0.73
G 90			89.4	±0.77
G 95			94.4	±0.81

Table 9-7: JIS B2401 Sizes

JIS B2401 Sizes (Continued)

JIS B2401	Thickness		Inner Diameter	
	W (mm)		d (mm)	
G 100	3.1	±0.10	99.4	±0.85
G 105			104.4	±0.87
G 110			109.4	±0.91
G 115			114.4	±0.94
G 120			119.4	±0.98
G 125			124.4	±1.01
G 130			129.4	±1.05
G 135			134.4	±1.08
G 140			139.4	±1.12
G 145			144.4	±1.16
G 150	5.7	±0.13	149.3	±1.19
G 155			154.3	±1.23
G 160			159.3	±1.26
G 165			164.3	±1.30
G 170			169.3	±1.33
G 175			174.3	±1.37
G 180			179.3	±1.40
G 185			184.3	±1.44
G 190			189.3	±1.47
G 195			194.3	±1.51

JIS B2401	Thickness		Inner Diameter	
	W (mm)		d (mm)	
G 200	5.7	±0.13	199.3	±1.55
G 205			204.3	±1.58
G 210			209.3	±1.61
G 215			214.3	±1.64
G 220			219.3	±1.68
G 225			224.3	±1.71
G 230			229.3	±1.73
G 235			234.3	±1.77
G 240			239.3	±1.81
G 245			244.3	±1.84
G 250	5.7	±0.13	249.3	±1.88
G 255			254.3	±1.91
G 260			259.3	±1.94
G 265			264.3	±1.97
G 270			269.3	±2.01
G 275			274.3	±2.04
G 280			279.3	±2.07
G 285			284.3	±2.10
G 290			289.3	±2.14
G 295			294.3	±2.17

JIS B2401	Thickness		Inner Diameter	
	W (mm)		d (mm)	
G 300	5.7	±0.13	299.3	±2.20
G 305			304.3	±2.24
G 310			309.3	±2.27
G 315			314.3	±2.30
G 320			319.3	±2.33
G 325			324.3	±2.36
G 330			329.3	±2.39
G 335			334.3	±2.42
G 340			339.3	±2.45
G 345			344.3	±2.48
G 350	5.7	±0.13	349.3	±2.51
G 355			354.3	±2.54
G 360			359.3	±2.57
G 365			364.3	±2.60
G 370			369.3	±2.63
G 375			374.3	±2.67
G 380			379.3	±2.70
G 385			384.3	±2.73
G 390			389.3	±2.76
G 395			394.3	±2.79
G 400	399.3	±2.82		